

LIFAN 1P60FV/1P64FV/1P68FV

SPECIFICATION



Model:1P60FV(CE/EC, EPA/CARB) (4.0PS)

Engine type: 4-stroke single-cylinder with air-cooled

Bore*stroke: 60mm*42mm

Displacement: 118ml

Compression ratio: 8.0:1

Max power output: 2.8kw/3600rpm

Recommend power using: 1.8kw/3600rpm

Max torque: 5.2N.m/2500rpm

Ignition system: Non-contact transistorized ignition(TCI)

Start model: Recoil and hand-operated

Air cleaner: Semi-dry type

Fuel tank capacity: 1.8L

Fuel consumption: 395g/kw.h

Engine oil capacity: 0.6L

Dimension(L*W*H mm): 415*345*350

Dry weight: 11.5kg

Carton dimension(L*W*H mm): 470*430*395

QTY/20GP: 325

QTY/40GP: 675

QTY/40HQ: -

Model:1P64FV (CE/EC, EPA) (5PS)

Engine type: 4-stroke single-cylinder with air-cooled

Bore*stroke: 64mm*42mm

Displacement: 135ml

Compression ratio: 8.0:1

Max power output: 3.7kw/3600rpm

Recommnded power using: 2.3kw/3600rpm

Max torque: 6.6N.m/2500rpm

Ignition system: Non-contact transistorized ignition(TCI)

Start model: Recoil and hand-operated

Air cleaner: Semi-dry type

Fuel tank capacity: 1.8L

Fuel consumption: 395g/kw.h

Engine oil capacity: 0.6L

Dimension(L*W*H mm): 415*345*350

Dry weight: 14kg/12kg

Carton dimension(L*W*H mm): 470*430*395

QTY/20GP: 325

QTY/40GP: 675

QTY/40HQ: -

Model:1P68FV(CE/EC, EPA)(5.5PS)

Engine type: 4-stroke single-cylinder with air-cooled

Bore*stroke: 68mm*45mm

Displacement: 163ml

Compression ratio: 8.0:1

Max power output: 4.1kw/3600rpm

Recommded power using: 2.8kw/3600rpm

Max torque: 9.0N.m/2500rpm

Ignition system: Non-contact transistorized ignition(TCI)

Start model: Recoil and hand-operated

Air cleaner: Semi-dry type

Fuel tank capacity: 2.0L

Fuel consumption: 395g/kw.h

Engine oil capacity: 0.6L

Dimension(L*W*H mm): 415*345*350

Dry weight: 16kg

Carton dimension(L*W*H mm): 470*430*395

QTY/20GP: 325

QTY/40GP: 675

QTY/40HQ: -