



LIFAN 1P60FV-C, LIFAN 1P64FV-C

SPECIFICATION

Model:1P60FV-C (CE/EC, EPA)(4PS)

Engine type: 4-stroke single-cylinder with air-cooled

Bore*stroke: 60mm*42mm

Displacement: 118ml

Compression ratio: 8.0:1

Max power output: 2.8kw/3600rpm

Recommend power using: 1.8kw/3600rpm

Max torque: 5.2N.m/2500rpm

Ignition system: Non-contact transistorized ignition(TCI)

Start model: Recoil and hand-operated

Air cleaner: Semi-dry type

Fuel tank capacity: 1.8L

Fuel consumption: 395g/kw.h

Engine oil capacity: 0.6L

Dimension(L*W*H mm): 415*345*350

Dry weight: 11.5kg

Carton dimension(L*W*H mm): 470*430*395

QTY/20GP: 325

QTY/40GP: 675

QTY/40HQ: -

Model:1P64FV-C(CE/EC, EPA)(5PS)

Engine type: 4-stroke single-cylinder with air-cooled

Bore*stroke: 64mm*42mm

Displacement: 135ml

Compression ratio: 8.0:1

Max power output: 3.7kw/3600rpm

Recommded power using: 2.3kw/3600rpm

Max torque: 6.6N.m/2500rpm

Ignition system: Non-contact transistorized ignition(TCI)

Start model: Recoil and hand-operated

Air cleaner: Semi-dry type

Fuel tank capacity: 1.8L

Fuel consumption: 395g/kw.h

Engine oil capacity: 0.6L

Dimension(L*W*H mm): 415*345*350

Dry weight: 14kg/12kg

Carton dimension(L*W*H mm): 470*430*395

QTY/20GP: 325

QTY/40GP: 675

QTY/40HQ: -